



Désignation	Dimensions principales (mm)					Charges nominales de base	
	d	D	B	C	T	Dynamique	Statique
D103	□	103	□	9.4	□	18400	19900
D103/YA	□	103	□	9.4	□	18400	19900
D113/YA	□	113	□	9	□	22410	24620
D113/YB	□	113	□	9	□	22410	24620
D114	□	114	□	9	□	12710	19940
D116	□	116	□	8.5	□	23000	26060
D125	□	125	□	9	□	26890	32180
D114/YA	□	114	□	8.6	□	28850	35820
0145/YA	□	145	□	11	□	31590	37410
D148	□	148	□	9.4	□	32540	39520
D148/YA	□	148	□	9.2	□	32540	39520
D165/YA	□	165	□	10.1	□	42720	52480
D171	□	171	□	0.1	□	43040	63830
D171YA	□	171	□	10	□	43040	53830
D186/VA	□	186	□	10.9	□	50270	65140
D233	□	233	□	15.1	□	79910	10120
D258	□	258	□	15	□	98260	133330
SRG90	70	90	10.5	7	10	5840	17210
SRG113	87	113	12.5	9	12.5	22300	24600
SRG114	89	114	10	9	13	12710	9940

## RV reducer main bearings

SRYA114	89	114	9	9	12	12710	19940
SRG120	97	120	13.5	10	13	20250	24300
SR140	115	40	10.2	6.5	10	20530	28130
SR145	115	45	5.05	11	15	31460	37370
SR147	115	47	4.25	10.625	4.25	31460	37370
SR147/YA	115	47	13.9	10.625	14.2	31460	37370
SR147/VB	115	147	14.2	10.6	14.1	31460	37370
SR153	129	153	14.3	11	14	26890	36810
SR165/YA	30	165	4.75	11	15	55100	45850
SRG165/YB	131	165	15.2	11	15	42000	51000