



| Dimensions principales (mm) | | | Désignation | Charges nominales de base | | Vitesse limitée | | Poids (kg) |
|-----------------------------|----|----|-------------|---------------------------|----------|-----------------|-------|------------|
| d | D | B | | Dynamique | Statique | Graisse | Huile | |
| 17 | 30 | 7 | 71903C | 5 | 2.94 | 41000 | 62000 | 0.02 |
| 17 | 30 | 7 | 71903AC | 4.75 | 2.8 | 36000 | 54000 | 0.02 |
| 20 | 37 | 9 | 71904C | 6.95 | 4.25 | 37000 | 55000 | 0.04 |
| 20 | 37 | 9 | 71904AC | 6.6 | 4.05 | 30000 | 45000 | 0.04 |
| 25 | 42 | 9 | 71905C | 0.85 | 5.4 | 28500 | 41500 | 0.045 |
| 25 | 42 | 9 | 71905AC | 7.45 | 5.15 | 25000 | 38000 | 0.045 |
| 30 | 47 | 9 | 71906C | 8.3 | 6.25 | 25000 | 37000 | 0.05 |
| 30 | 47 | 9 | 71906AC | 7.85 | 5.95 | 22000 | 33000 | 0.05 |
| 35 | 55 | 10 | 719070 | 12.1 | 9.15 | 21000 | 33000 | 0.075 |
| 35 | 55 | 10 | 71907AC | 11.4 | 8.7 | 19000 | 28000 | 0.075 |
| 40 | 62 | 12 | 71908C | 15.1 | 11.7 | 18000 | 28000 | 0.11 |
| 40 | 62 | 12 | 71908AC | 14.3 | 11.2 | 16500 | 25000 | 0.11 |
| 45 | 68 | 12 | 71909C | 16 | 13.4 | 16000 | 25000 | 0.13 |
| 45 | 68 | 12 | 71909AC | 5.1 | 12.7 | 15000 | 23000 | 0.13 |
| 50 | 72 | 12 | 71910C | 6.9 | 15 | 15000 | 23000 | 0.13 |
| 50 | 72 | 12 | 71910AC | 5.9 | 14.2 | 14000 | 21000 | 0.135 |
| 55 | 80 | 13 | 71911C | 19.1 | 17.7 | 12500 | 20000 | 0.185 |
| 55 | 80 | 13 | 71911AC | 18.1 | 16.8 | 11500 | 18000 | 0.185 |
| 60 | 85 | 13 | 71912C | 19.4 | 18.7 | 11500 | 18000 | 0.195 |

Precision Angular Contact Ball Bearings 719 Series

| | | | | | | | | |
|----|-----|----|---------|------|------|-------|-------|-------|
| 60 | 85 | 13 | 71912AC | 18.3 | 17.7 | 11000 | 17000 | 0.195 |
| 65 | 90 | 13 | 71913C | 20.2 | 20.5 | 10800 | 16500 | 0.21 |
| 65 | 90 | 13 | 71913AC | 9.1 | 19.4 | 10500 | 15000 | 0.21 |
| 70 | 100 | 16 | 71914C | 28.1 | 27.8 | 10500 | 15000 | 0.34 |
| 70 | 100 | 16 | 71914AC | 26.5 | 26.3 | 10000 | 14500 | 0.34 |
| 75 | 105 | 16 | 71915C | 28.6 | 29.3 | 9200 | 14500 | 0.36 |
| 75 | 105 | 16 | 71915AC | 26.9 | 27.7 | 8500 | 14000 | 0.36 |
| 80 | 110 | 16 | 71916C | 29 | 30.5 | 12200 | 18500 | 0.38 |
| 80 | 110 | 16 | 71916AC | 27.3 | 29 | 10600 | 15800 | 0.38 |
| 85 | 120 | 18 | 71917C | 39 | 40.5 | 11300 | 17100 | 0.53 |
| 85 | 120 | 18 | 71917AC | 36.5 | 38.5 | 9800 | 14700 | 0.54 |